Technical Data Sheet 10mm 100% Wool Design Felt

| C.DO | ヘけいへん | ations |
|---------|------------|------------|
| . 71.11 | (.!!!(.~ | 111() 15 |
| | | |

| Name | 100% Wool Design Felt | |
|---------------------|-----------------------|--|
| Thickness | 10 mm (3/8 in) | |
| Thickness Tolerance | ±0.5 mm (±1/5 in) | |
| Content | 100% Merino Wool | |
| Country of Origin | Germany | |
| Width | 160 cm (63 in) | |
| | , | |
| Width Tolerance | ±4 cm (±1 3/5 in) | |

Performance Characteristics

| Colorfastness to Light (AATCC Method 16-2004, Option 3) | Class 4 (60 hours) |
|---|--------------------------------|
| Colorfastness to Wet & Dry Crocking (AATCC 8-2007) | Class 4.5 (Wet), Class 4 (Dry) |

Flammability

| Surface Burning Characteristics of Building Materials (ASTM E84 – Unadhered) | Class A |
|---|---------|
| Euroclass Flameproof to EN 13501-1 | Pass |

Environmental

| Oeko-Tex® Standard 100 Certified | Product Class II |
|----------------------------------|------------------|

Recommended Cleaning Instructions

Vacuum occasionally to remove general air-borne debris. Should soiling occur, clean with a mild, water-free dry cleaning solvent. We recommend consulting a professional cleaning service to obtain proper care and maintenance.

