

# Anchor™ Storage

## Capability and Limitation Guidelines

### Finishes

- ▶ No custom laminate outside the Knoll Core Laminate offering of 15 standard options.
- ▶ Mixing Knoll Core Laminates on units is an option available with the September 2013 CAP release; refer to Mixed Laminate Finishes section in price list.
- ▶ Veneer and powder on wood finishes are not supported.

### Design Details

- ▶ Customer's own pull options can be accommodated.
- ▶ No integrated pull-style drawer fronts can be supported (i.e. no Ref J-pull).

### Custom Sizes

#### Credenzas:

- ▶ WIDTH: Overall widths of credenzas may be increased or decreased, but the difference will only impact the width of the open cavity. Widths of box and/or file drawer openings may not be adjusted. Maximum overall credenza width is 96". Credenzas without an open section (i.e. 60" wide credenza with Box/File 30, Box/File 30) may not be customized in width.
- ▶ DEPTH: Overall depth of credenzas may be increased. If the unit contains a box and/or file drawer, the interior cavity depth will increase but the size of the drawer bodies will remain the same. Minimum depth is 20" (nominal).
- ▶ HEIGHT: Standard height of credenza must be maintained (22" nominal).

#### Doublewide Pedestals:

- ▶ WIDTH: Overall width of the All Open unit may be increased or decreased. All other doublewide pedestals contain box and/or file drawers and may not be adjusted in width.
- ▶ DEPTH: Overall depth of doublewide pedestals may be increased. If the unit contains a box and/or file drawer, the interior cavity depth will increase but the size of the drawer bodies will remain the same. Minimum depth is 20" (nominal).
- ▶ HEIGHT: Standard height of doublewide pedestals must be maintained (28" nominal including top).

#### Lockers:

- ▶ WIDTH: Overall width may be modified up to 18" wide maximum.
- ▶ DEPTH: Overall depth may be modified up to 30" deep maximum.
- ▶ HEIGHT: Overall height may be modified up to 78" maximum.
- ▶ The number of doors on a locker may be customized, however doors must be at least 22" high.